



期偉有限公司
MIRACLE CO., LTD.

P.O. Box 21-111, Taipei 103, Taiwan

OFFICE: TEL:02-25940224, FAX:886-2-25944047
TAIPEI, TAIWAN
LIAISON:TEL: 04-24715429, FAX:886-4-24714429
TAICHUNG, TAIWAN
PLANT: TEL:07-3533476, FAX:886-7-3533544
KAOHSIUNG, TAIWAN
E-MAIL: miracle83@seed.net.tw

AMSTRON® Microprocessor-Based Hand-held Immersion Digital Pyrometer Model PM

Specification :

1. Unit: ° C / ° F.
2. Display: 4 digit, 7 segment, 0.43" height LED.
3. Measuring mode: Track & Hold, Continuous.
4. Measuring range:

Track & Hold	Continuous
S T/C: 400~1770 ° C	S T/C: Room temperature ~1770 ° C
R T/C: 400~1770 ° C	R T/C: Room temperature ~1770 ° C
B T/C: 400~1820 ° C	B T/C: 100 ~1820 ° C
5. Accuracy: ± 1 ° C or ± 1 ° F.
6. Status display: Green LED(Ready), Yellow(Measuring), Red(Done).
7. Trouble-shooting :
 - (1) [-tc-] : T/C burnout or poor contact
 - (2) [lobt] : Low battery
 - (3) [HIGH] :Temperature over measuring range.
8. Battery: Long life Ni-H rechargeable (without memory-effect).
9. Power consumption: 0.8W.
10. AC adapter: 110VAC, or 220VAC.
11. Dimension : 115 x 170 x 200mm Height (net weight:1.8kg without lance)



Pm6t